



RAVENOL High Fuel Economy HFE SAE 5W-16



1L | 1111104-001

4L | 1111104-004

10L | 1111104-010

20L | 1111104-020

Kategorie: Passenger car motor oil

Artikelnummer: 1111104

Viscosity: 5W-16

Specifications: API SN

Oil type: Full synthetic

Recommendations: Honda 08215-99974, Honda 08216-99974, Honda 08232-P99S1LHE, Honda Ultra Green, Honda Ultra Next, Mitsubishi Dia Queen ECO Plus, Mitsubishi MZ102661, Mitsubishi MZ102662, Nissan KLANM-01A04 Extra Save X Eco Hybrid Engine, Toyota 08880-11005

Application: Passenger car

Technology: CleanSynto, USVO

RAVENOL High Fuel Economy HFE SAE 5W-16 is a PAO (Polyalphaolefin) based, full synthetic low friction motor oil with especially USVO® and proven CleanSynto® technology for passenger car petrol engines with and without turbo-charging and direct injection.

Due to the USVO® technology we achieve an extremely high viscosity stability. We avoid the disadvantages of polymeric viscosity improvers while taking advantage of them. This improves engine protection, performance, engine cleanliness and oil drain intervals. The USVO® technology makes it possible that the product has no shear losses during the entire change interval and is extremely stable to oxidation. This unique technology helps oil lubricate faster, thereby minimizing friction while keeping the engine clean and efficient.

RAVENOL High Fuel Economy HFE SAE 5W-16 was formulated with tri-nuclear molybdenum and OFM (Organic Friction Modifiers), in order to achieve minimal friction, wear and fuel consumption with excellent cold start characteristics.

With its new formulation, **RAVENOL High Fuel Economy HFE SAE 5W-16** provides a safe layer of lubrication even at very high operating temperatures and protects from corrosion and loss of oil through oxidation or coking. The excellent cold start behavior ensures optimum lubrication safety during the cold running phase.

By significantly reducing fuel consumption, **RAVENOL High Fuel Economy HFE SAE 5W-16** helps to protect the environment by reducing emissions.

Extended oil change intervals according to the manufacturer's instructions.

Application instructions

RAVENOL High Fuel Economy HFE SAE 5W-16 is suitable as a high performance, smooth-running engine oil for sophisticated engines. It is recommended for modern passenger car petrol engines, if the engine manufacturer recommends using a low viscosity oil with the viscosity category SAE 5W-16. It is also suitable for use in hybrid vehicles from various manufacturers.

Characteristics

- Fuel saving in partial and full load operation.
- Excellent wear protection and a high viscosity index ensure the long service life of the engine even under high speed driving conditions.
- Excellent cold start properties even at low temperatures of below -30°C.
- A reliable lubrication film even at high operating temperatures.
- Low volatility, resulting in low oil consumption.
- No oil-related deposits in combustion chambers, in the piston ring zone and on valves.
- Compatible with sealing materials.
- Extended oil change intervals protect natural resources.
- Ideal for hybrid vehicles.

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AU
Colour		gelb-braun	VIS
Sulphated Ash	%wt.	0,9	DIN
tbn	mg KOH/g	8,2	AST
Viscosity at 100 °C	mm ² /s	7,5	DIN
Viscosity at 40 °C	mm ² /s	41,6	DIN
Viscosity Index VI		148	DIN
CCS Viscosity at -30 °C	mPa*s	4461	AST
Density at 20 °C	kg/m ³	848,0	EN
Flashpoint	°C	240	DIN
HTHS Viscosity at 150 °C	mPa*s	2,5	AST
Low Temp. Pumping viscosity (MRV) at -35 °C	mPa*s	8.200	AST
Noack Volatility	% M/M	5,7	AST
Pourpoint	°C	-39	DIN