



RAVENOL ATV-UTV 4T SAE 5W-40



1L | 1152161-001
4L | 1152161-004
10L | 1152161-010
20L | 1152161-020
20L | 1152161-B20
60L | 1152161-060
60L | 1152161-D60
208L | 1152161-208
208L | 1152161-D28
1000L | 1152161-700

Kategorie: 4 stroke engine oil

Artikelnummer: 1152161

Specifications: API SN, JASO MA2

Oil type: Synthetic

Recommendations: Bombardier, CAN-AM, CFMOTO, Honda, Kawasaki, Polaris, Suzuki, Yamaha

RAVENOL ATV-UTV 4T SAE 5W-40 is especially developed for demanding use in quads and ATVs (off-road vehicles). It is used for maximum performance and optimum protection in 4-stroke quad engines. Special additives reliably protect the transmission against wear and ease the cranking process with the gear engaged as well as the shifting process itself.

RAVENOL ATV-UTV 4T SAE 5W-40 enables a low-wear cold start even at very low outside temperatures thanks to its high viscosity. Wear is also minimized in lower gears and with high engine loads.

RAVENOL ATV-UTV 4T SAE 5W-40 is blended with special additives which reliably protect the gearbox against wear even under high loads and counteract any combustion chamber deposits in the engine.

Application instructions

RAVENOL ATV-UTV 4T SAE 5W-40 is used in 4-stroke quad engines from leading manufacturers. It can also be used in vehicles with wet clutches and catalytic converters. It is suitable as an all-year-round oil for quads, but also for other ATV and Enduro vehicles.

RAVENOL ATV-UTV 4T SAE 5W-40 is designed for all air- and water-cooled 4-stroke engines in the ATV and Enduro range, in accordance to the vehicle manufacturer's operating instructions.

Besides many other vehicles suitable for:

Can-Am (BRP): Maverick (incl. R), Commander, Defender, DS, Renegade, Traxter, Outlander, etc.

Yamaha: Wolverine, Kodiak, Grizzly, Viking, etc.

Honda: FourTrax, Talon, Pioneer, etc.

Kawasaki: Brute Force, Mule, Teryx, KFX, etc.

Polaris: Ranger (gasoline), RZR, Sportsman, Pro XD, Predator, Crew, General, etc.

Suzuki: KingQuad, QuadSport, LTZ, etc.

CFMoto: CFORCE, UFORCE, ZFORCE, etc.

The manufacturer's instructions must be followed!

Characteristics

- low-wear cold start even at extremely low outside temperatures
- stable lubrication and good shear stability
- compatible with wet clutches and catalytic converters
- can be used all year round
- high corrosion- and wear protection
- low evaporation tendency, therefore low oil consumption
- tested and proven additives
- high safety reserves during peak loads

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
Sulphated Ash	%wt.	0,87	DIN 51575
tbn	mg KOH/g	7,2	ASTM D2896
Viscosity at 100 °C	mm ² /s	13,68	DIN 51562-1
Viscosity at 40 °C	mm ² /s	82,97	DIN 51562-1
Viscosity Index VI		169	DIN ISO 2909
CCS Viscosity at -30 °C	mPa*s	5937	ASTM D5293
Density at 20 °C	kg/m ³	847	EN ISO 12185
Flashpoint	°C	244	DIN EN ISO 2592
Noack Volatility	%m	5,8	ASTM D5800
Pourpoint	°C	-39	DIN ISO 3016