



# RAVENOL ATV-UTV 4T SAE 10W-50



1L | 1152162-001

4L | 1152162-004

10L | 1152162-010

20L | 1152162-020

20L | 1152162-B20

60L | 1152162-060

60L | 1152162-D60

208L | 1152162-208

208L | 1152162-D28

1000L | 1152162-700

**Kategorie:** 4 stroke engine oil

**Artikelnummer:** 1152162

**Specifications:** API SN, JASO MA2

**Oil type:** Synthetic

**Recommendations:** Bombardier, CAN-AM, CFMOTO, Honda, Kawasaki, Polaris, Suzuki, Yamaha

**RAVENOL ATV-UTV 4T SAE 10W-50** is especially developed for demanding use in quads and ATVs (off-road vehicles). It is used for maximum performance and optimum protection in 4-stroke quad engines. Special additives reliably protect the transmission against wear and ease the cranking process with the gear engaged as well as the shifting process itself.

**RAVENOL ATV-UTV 4T SAE 10W-50** enables a low-wear cold start even at very low outside temperatures thanks to its high viscosity. Wear is also minimized in lower gears and with high engine loads.

**RAVENOL ATV-UTV 4T SAE 10W-50** is blended with special additives which reliably protect the gearbox against wear even under high loads and counteract any combustion chamber deposits in the engine.

## Application instructions

**RAVENOL ATV-UTV 4T SAE 10W-50** is used in 4-stroke quad engines from leading manufacturers. It can also be used in vehicles with wet clutches and catalytic converters. It is suitable as an all-year-round oil for quads, but also for other ATV and Enduro vehicles.

**RAVENOL ATV-UTV 4T SAE 10W-50** is designed for all air- and water-cooled 4-stroke engines in the ATV and Enduro range, in accordance to the vehicle manufacturer's operating instructions.

Besides many other vehicles suitable for:

Can-Am (BRP): Maverick (incl. R), Commander, Defender, DS, Renegade, Traxter, Outlander, etc.

Yamaha: Wolverine, Kodiak, Grizzly, Viking, etc.

Honda: FourTrax, Talon, Pioneer, etc.

Kawasaki: Brute Force, Mule, Teryx, KFX, etc.

Polaris: Ranger (gasoline), RZR, Sportsman, Predator, Pro XD, Crew, General, etc.

Suzuki: KingQuad, QuadSport, LTZ, etc.

CFMoto: CFORCE, UFORCE, ZFORCE, etc.

The manufacturer's instructions must be followed!

## Characteristics

- Low-wear cold start even at extremely low outside temperatures
- Stable lubrication and good shear stability
- Compatible with wet clutches and catalytic converters
- Can be used all year round
- High corrosion- and wear protection
- Low evaporation tendency, therefore low oil consumption
- Tested and proven additives
- High safety reserves during peak loads

## Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		hellbraun	VISUELL
Sulphated Ash	%wt.	0,85	DIN 51575
tbn	mg KOH/g	7,6	ASTM D2896
Viscosity at 100 °C	mm <sup>2</sup> /s	17,6	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	120,4	DIN 51562-1
Viscosity Index VI		162	DIN ISO 2909
CCS Viscosity at -30 °C	mPa*s	5914	ASTM D5293
Density at 20 °C	kg/m <sup>3</sup>	854	EN ISO 12185
Flashpoint	°C	248	DIN EN ISO 2592
Noack Volatility	%m	5,2	ASTM D5800
Pourpoint	°C	-33	DIN ISO 3016