RAVENOL 2-Taktoel NOT SELFMIX

Kategorie: 2 stroke engine oil

Artikelnummer: 1153101

Specifications: API SA

Oil type: Mineral

Application: Hobby and garden, Motorcycle, Marine

RAVENOL 2-Takt-Öl NOT SELFMIX is mineral high quality two-stroke oil for conventional 2-stroke engines without self-mixing. This unblended oil is produced from carefully selected, pure mineral raffinates. It is resistant to oxidation, non-foaming and has excellent viscosity-temperature characteristics. Due to the low pourpoint, this oil can be used in low as well as high temperatures and ensures an impeccable lubrication.

1L | 1153101-001
4L | 1153101-004
10L | 1153101-010
20L | 1153101-020
20L | 1153101-B20
60L | 1153101-060
208L | 1153101-208
1000L | 1153101-700

Application instructions

RAVENOL 2-Takt-Öl NOT SELFMIX is applicable for all conventional two-stroke engines, for which self-mixing is not specified.

Characteristics

- Excellent viscosity-temperature characteristics
- Good shear stability
- Outstanding oxidation stability
- Good demulsification characteristics

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm²/s	15,7	DIN 51659-2
Viscosity at 40 °C	mm²/s	165,8	DIN 51659-2
Viscosity Index VI		97	DIN ISO 2909
Density at 20 °C	kg/m³	896,0	EN ISO 12185
Flashpoint	°C	254	DIN EN ISO 2592
Pourpoint	°C	-24	DIN ISO 3016