RAVENOL MARINE 1230 SAE 30 TBN12

Kategorie: Marine engine oil

Artikelnummer: 1163010

Viscosity: 30

Specifications: API CF

Oil type: Mineral

Recommendations: DEF-STAN 91-22/2, MIL -L-2104 C

Application: Marine

RAVENOL MARINE 1230 SAE 30 TBN12 is a mineral diesel engine oil for the navy.

RAVENOL MARINE 1230 SAE 30 TBN12 is made from high quality solvent refined basic oils with a special multi functional additivation for the demands of a navy oil for the use of navy diesel engines and for the lubrication of gear transfers in aggregates used on boats.

1L | 1163010-001
4L | 1163010-004
10L | 1163010-010
20L | 1163010-020
20L | 1163010-B20
60L | 1163010-060
208L | 1163010-208
1000L | 1163010-700

Application instructions

RAVENOL MARINE 1230 SAE 30 TBN12 is used as a lubrication oil in quickly running and so-called « medium speed » navy diesel engines, perhaps with turbo charging and when using distilled fuels.

Characteristics

- a very good oxidation resistance
- a stable viscosity index
- excellent dispersant and detergent characteristics
- a good neutralizing power to neutralize acid connections which occur when burning diesel fuels
- a good cleaning power
- a good corrosion protection
- a good foam prevention
- a low pourpoint
- a good water separation behaviour

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		braun	VISUELL
Sulphated Ash	%wt.	1,67	DIN 51575
tbn	mg KOH/g	12,5	ASTM D2896
Viscosity at 100 °C	mm^2/s	11,7	DIN 51659-2
Viscosity at 40 °C	mm^2/s	105,2	DIN 51659-2
Viscosity Index VI		99	DIN ISO 2909
Density at 20 °C	kg/m^3	883,0	EN ISO 12185
Flashpoint	°C	274	DIN EN ISO 2592
Pourpoint	°C	-33	DIN ISO 3016