RAVENOL MARINEOIL PETROL SAE 15W-40

Kategorie: Marine engine oil

Artikelnummer: 1163200

Viscosity: 15W-40

Specifications: API SL

Oil type: Mineral

Recommendations: Kohler, Mercruiser, VOLVO PENTA AB, Yanmar

Application: Marine

RAVENOL MARINEOIL PETROL SAE 15W-40 is a high additive treated HD engine oil for marine gasoline engines.

RAVENOL MARINEOIL PETROL SAE 15W-40 is especially produced for extended oil change intervals (under consideration of the manufacturer instruction).

1L | 1163200-001
4L | 1163200-004
10L | 1163200-010
20L | 1163200-020
20L | 1163200-B20
60L | 1163200-060
208L | 1163200-208

Characteristics

- an extreme high pressure absorption capacity
- a very high oxidation stability
- an excellent aging resistance
- an excellent viscosity temperature behaviour
- high safety reserves also under boundary lubrication conditions
- suitability for extended oil change intervals
- suitability for complicate operating conditions

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		blau	VISUELL
tbn	mg KOH/g	10,5	ASTM D2896
Viscosity at 100 °C	mm²/s	15,0	DIN 51659-2
Viscosity at 40 °C	mm²/s	115,7	DIN 51659-2
Viscosity Index VI		134	DIN ISO 2909
Density at 20 °C	kg/m³	879,5	EN ISO 12185
Flashpoint	°C	238	DIN EN ISO 2592
Pourpoint	°C	-36	DIN ISO 3016