RAVENOL ATF Fluid

Kategorie: Gear oil for automatic transmissions

Artikelnummer: 1213101

Oil type: Mineral

Recommendations: Allison C4, Caterpillar TO-2, DTFR 13C120 (236.2), MAN 339 A, MB 236.2, Renk Doromat, Type A Suffix A (TASA)

Application: Oldtimer, Passenger car

RAVENOL ATF Fluid is designed on the basis of mineral refined base oils with a special additive and inhibition, which guarantee a perfect function.

RAVENOL ATF Fluid is a very high quality mineral gear fluid for automatic fluid couplings and torque converters as well as power steering aids.

1L | 1213101-001
4L | 1213101-004
10L | 1213101-010
20L | 1213101-020
20L | 1213101-B20
60L | 1213101-060
208L | 1213101-208
1000L | 1213101-700

Application instructions

RAVENOL ATF Fluid should be used according to the instructions of the unit manufacturer in: Automatic transmissions, turbo couplings, servo clutches and other hydrostatic and hydrodynamic systems.

RAVENOL ATF Fluid must not be used if ATF Type DEXRON B or DEXRON D or ATF Type M2C-33 E / F / G are expressly mentioned as filling instructions.

Characteristics

- Exceptionally good resistance to aging
- A very good viscosity-temperature behaviour
- Effective protection against wear
- Very good oxidation stability and low foaming tendency
- Enhanced protection against corrosion
- An extremely low pour point
- Compatible with all types of sealing materials
- Miscibility and compatibility with all brands of ATF's with Type A Suffix A specification

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		Rot	VISUELL
Viscosity at 100 °C	mm^2/s	7,4	DIN 51659-2
Viscosity at 40 °C	mm^2/s	34,6	DIN 51659-2
Viscosity Index VI		187	DIN ISO 2909
Density at 20 °C	kg/m^3	848,0	EN ISO 12185
Flashpoint	°C	210	DIN EN ISO 2592
Pourpoint	°C	-48	DIN ISO 3016