



RAVENOL Agrar Synto SAE 15W-40

Kategorie: Engine oil for agricultural vehicles and construct

Artikelnummer: 1310252

Viscosity: 15W-40

Specifications: ACEA A3/B4, ACEA E7, API CI-4, API SL, JASO DH-1

Oil type: Mineral

Recommendations: Allison C4, API CI-4, API SL, Caterpillar TO-2, Cummins CES 20076, Cummins CES 20077, Cummins CES 20078, Deutz DQC III-10, DTFR 15B110, Global DHD-1, IVECO, JASO DH-1, John Deere JDQ-78A, Mack EO-M, Mack EO-M Plus, MAN M 3275-1 (Multigrades), MB 228.3, MB 229.1, MTU Typ 2, Renault RLD/RLD-2, Scania LDF-2, STEYR Motor GAZ 560, TEDOM 258-3 (61-0-0258), VOLVO VDS-3, YaMZ, ZF TE-ML 07C



10L | 1310252-010

20L | 1310252-020

20L | 1310252-B20

60L | 1310252-060

60L | 1310252-D60

208L | 1310252-208

208L | 1310252-D28

1000L | 1310252-700

RAVENOL Agrar Synto SAE 15W-40 is an SHPD engine oil for mixed fleets of agricultural vehicles. Particularly suitable for year-round use in all agricultural vehicles.

RAVENOL Agrar Synto SAE 15W-40 can also be used in agricultural diesel engines with turbochargers. It is suitable for modern diesel vehicles that comply with the EURO V emissions standard.

RAVENOL Agrar Synto SAE 15W-40 has been specially developed for extended oil change intervals (in accordance with the manufacturer's specifications) and thus increases cost-effectiveness in continuous use.

Application instructions

RAVENOL Agrar Synto SAE 15W-40 is used as an agricultural all-season multigrade engine oil in highly stressed agricultural diesel engines with or without turbocharging.

RAVENOL Agrar Synto SAE 15W-40 is recommended as a universal agricultural diesel engine oil for continuous use due to its extended oil change intervals, good cold start properties, EURO V compliance and resistance to aging.

Characteristics

- Extremely high pressure absorption capacity, very high oxidation stability
- Universally suitable for agricultural vehicles, especially with turbo diesel engines
- Excellent aging resistance
- Outstanding viscosity-temperature behavior
- High safety reserves even under marginal lubrication conditions
- Suitable for extended oil change intervals
- Ideally suited for demanding operating conditions

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		gelbbraun	VISUELL
tbn	mg KOH/g	10,5	ASTM D2896
Viscosity at 100 °C	mm ² /s	15,0	DIN 51562-1
Viscosity at 40 °C	mm ² /s	115,7	DIN 51562-1
Viscosity Index VI		134	DIN ISO 2909
Density at 20 °C	kg/m ³	870	EN ISO 12185
Flashpoint	°C	238	DIN EN ISO 2592
HTHS Viscosity at 150 °C	mPa*s	4,0	ASTM D5481
Pourpoint	°C	-36	DIN ISO 3016