



RAVENOL Mehrzweckfett OML

Kategorie: Grease

Artikelnummer: 1340101

Specifications: DIN 51502: K2K-30, ISO 6743-9: ISO-L-XCCEA2

Application: Industry, Passenger car, Truck, Agricultural machinery

RAVENOL Mehrzweckfett OML is lithium saponified multipurpose grease with oxidation and corrosion protective additives.

RAVENOL Mehrzweckfett OML has an extreme mechanical stability and a very low friction value. Therefore it can be transported easily.



Application instructions

RAVENOL Mehrzweckfett OML is used for the lubrication of easy loaded antifriction bearings and machine components. It is also suited as multipurpose lubrication grease for vehicles.

Characteristics

- Universal use, multipurpose characteristic for a mixed car pool
- Extreme shear stability
- Excellent corrosion protection
- Excellent wear protection
- Very good mechanical and chemical stability
- Very good aging resistant
- Good pumpability, even at low temperatures

5L | 1340101-005

15L | 1340101-015

100L | 1340101-100

180L | 1340101-180

400L | 1340101-400

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA
Colour		hellbraun
Dropping Point	°C	>180
Thickener		Lithium-Komplexseifen
VKA Pressure Carrying Capacity	N	2000 - 2200
Worked Penetration at 60 Strokes	mm/10/25°C	265-295
Water Resistance (3h/90 °C)	°C	1-90
Working Temperature	°C	-30 / +120
Kinematic Viscosity (Base Oil) at 40 °C	mm ² /s	130
Corrosion (SKF Emcor dist. Water)	Korr. Grad	1
Copper Corrosion (24h/120 °C)		1
Short term temperature up to	°C	130
NLGI-Class		2
Product Classification		K2K-30