RAVENOL Polfett - Säureschutzfett

Kategorie: Grease

Artikelnummer: 1340115

Specifications: DIN 51502: K2K-30, ISO 6743-9: ISO-L-XCCEA2

Application: Industry, Passenger car, Truck, Motorcycle, Marine, Agricultural machinery

100L | 1340115-100

RAVENOL Polfett-Säureschutzfett is lithium saponified multipurpose grease with oxidation and corrosion protective additives.

RAVENOL Polfett-Säureschutzfett has an extreme mechanical stability.

Application instructions

RAVENOL Polfett-Säureschutzfett is used for the protection of contacts and metal parts against corrosion caused by aggressive media (acids).

Characteristics

- Extreme shear stability
- Very good mechanical and chemical stability
- Excellent wear protection
- Very good aging resistant
- Excellent corrosion protection
- Good pumpability, even at low temperatures

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
Colour		hellbraun	VISUELL
Dropping Point	°C	>180	DIN ISO 2176
Thickener		Lithium-Komplexseifen	DIN 51757
VKA Pressure Carrying Capacity	N	2000 - 2200	DIN 51350-4
Worked Penetration at 60 Strokes	mm/10/25°C	265-295	ISO 2137
Water Resistance (3h/90 °C)	°C	1-90	DIN 51807-1
Working Temperature	°C	-30 / +120	DIN 51825
Kinematic Viscosity (Base Oil) at 40 °C	mm²/s	130	DIN 51659-2
Corrosion (SKF Emcor dist. Water)	Korr. Grad	1	DIN 51802
Copper Corrosion (24h/120 °C)		1	DIN 51811
Short term temperature up to	°C	130	DIN 51757
NLGI-Class		2	DIN 51818
Product Classification		K2K-30	DIN 51502