

RAVENOL Grease-Spray

Kategorie: Car care products

Artikelnummer: 1340190



400L | 1340190-400

RAVENOL Grease Spray is a high-quality, light-colored lubricating grease in a practical aerosol form for reliable long-term and continuous lubrication of mechanical components. Unlike conventional spray oils, it forms a highly adhesive grease layer after spraying, thus ensuring effective grease lubrication even over longer periods of time.

RAVENOL Grease Spray also enters hard-to-reach areas of the components onto which it is sprayed thanks to its excellent creep properties. After application, it forms a stable and resilient lubricating film that reduces friction, minimizes wear and tear, and reliably prevents squeaking and creaking noises.

RAVENOL Grease Spray cleans soiled metal surfaces and leaves behind a long-lasting, ultra-thin film that neither smears nor sticks and does not attract dust. This film protects and maintains tools, machines and electrical and mechanical equipment while keeping them in good working order.

RAVENOL Grease Spray is suitable for lubricating joints, bushings, bearings, hinges, slide rails, and similar components. At high temperatures, slight dark discoloration and a paraffinic odor may occur, but this does not impair the lubricating properties.

Application instructions

RAVENOL Grease Spray must be shaken thoroughly before use and the can must be held upright or slightly inclined during application.

RAVENOL Grease Spray should only be applied to dry, clean components without any lubricant residues. Spray on from a distance of approx. 20-30 cm and allow to take effect. RAVENOL Brake Cleaner is suitable for degreasing beforehand, and RAVENOL Sealant Remover can be used for stubborn residues. Only use on parts or components that are not under power during application.

Note:

Do not store under pressure, above +50°C or in direct sunlight.

Characteristics

- Versatile applications such as: joints, bushings, bearings, hinges, slide rails, and much more
- Ensures consistent permanent lubrication
- Very high temperature stability
- Anti-corrosive and anti-oxidative
- Propellant: propane/butane
- Very well suited for delicate components
- Eliminates squeaking and creaking
- Based on paraffin-based, medical-grade mineral oil
- Purity complies with DAB 1996

Technical Product Data

CHARACTERISTICS	PROPERTY	DATA	AUDIT
	mm ² /s	21-26	
Color		weiß / white	VISUELL
Flashpoint (PM)	°Celsius	min. 180	
Working Temperature	°Celsius	bis +250	
Short term temperature up to	°Celsius	285	
Odour		neutral	